



FIREPROTECT

Data Sheet

Fireprotect House
Factory Road
Sandycroft
Deeside
Flintshire
CH5 2QJ

Tel:- 01244 536595
Fax:- 01244 533592
e-mail:- sales@fireprotect.co.uk
Web:- <http://www.fireprotect.co.uk>

Fast Wrap XL

Manufacturers & Suppliers of Passive Fire Protection Products

Fast Wrap XL is a flexible blanket composed of high temperature

fibres classified for applications to 1200°C and fully encapsulated in a durable glass fibre reinforced aluminium foil facing for easy handling and installation.

The foil encapsulation of the blanket prevents water, moisture or grease ingress ensuring good integrity and avoiding promotion of mould growth.

The core fibres in FastWrap XL are manufactured using fibres which are an alkaline earth silicate wool with low biopersistence exonerated from carcinogenic classification under Nota Q of the European Union Directive 97/69/EC.

Features

Thin and lightweight at 38mm thick, 96kg/m³ density

Contours easily to complex duct designs

Fully foil encapsulated for fast and clean installation

Contains 1200°C rated fibre

Good sound absorption

A1 Reaction to Fire Classification in accordance with EN 13501-1

Applications

Fire Protection of ventilation ducting for up to 2 hours in accordance with ISO 6944, BS 476 part 24 and EN 1366-1 standards.



Physical Characteristics

Thickness	Length	Width
38 mm	4800 mm	610 mm
38 mm	4800 mm	1220 mm
38 mm	7620 mm	610 mm
38 mm	7620 mm	1220 mm

Storage

Fast Wrap XL should be stored in a dry warehouse environment on pallets. Pallets should not be stacked.

The Company reserve the right to update this data sheet should any additional information become available. As our products are being used for a variety of applications under different conditions, the Company will not be held responsible for the failure of any product. Whilst all information is provided in good faith, it is up to the customer to test and establish suitability of each product via their own test methods.