



FIREPROTECT

Data Sheet



Fireprotect House
Factory Road
Sandycroft
Deeside
Flintshire
CH5 2QJ

Tel:- 01244 536595
Fax:- 01244 533592
e-mail:- sales@fireprotect.co.uk
Web:- http://www.fireprotect.co.uk

System - 36/23 Plus

Manufacturers & Suppliers of Passive Fire Protection Products

System-36/23 PLUS is a flexible U-shaped glazing gasket designed for 60 minutes fire resistance in screens. Flexible enough to be fitted to curved corners and circular vision panels. Tested with many popular glass types. Supplied coiled in a box so it's easily dispensed and cut to length, reducing wastage.



LG2020



For unrebated screen frames.



Test evidence

Fire: BS EN 1634-1: 2014.
Fire: BS 476-22: 1987.

Performance

Provides 60 minutes fire resistance.

Size

30mm x 22.5mm.

Standard lengths

25m coils.

Seal material

Sodium silicate intumescent.

Finish

Black with white identification spine.

Glass thickness

Suitable for use with 23mm Pyrostop®, 23mm Pyranova® and 23mm Fireswiss Foam glass types.

Glass type

Please refer to Certifire certificate CF5060 for the full range of glass types.

Application

System for screens only.

Intumescent liner

No liner is required.

Glazing beads

Glazing beads are required on both sides of the glass.

Note: Hardwood or softwood beads are available (min density 550kg/m³).

Fixing of beads: Screwed using No.8 x 45mm countersunk screws at 200mm nom. centres.

Accreditation

