



FIREPROTECT

# Data Sheet



Fireprotect House  
Factory Road  
Sandycroft  
Deeside  
Flintshire  
CH5 2QJ

Tel:- 01244 536595  
Fax:- 01244 533592  
e-mail:- sales@fireprotect.co.uk  
Web:- http://www.fireprotect.co.uk

## System - 36/15 Plus

Manufacturers & Suppliers of Passive Fire Protection Products


System-36/15 PLUS is a flexible U-shaped glazing gasket designed for 60 minutes fire resistance in doors and screens. Flexible enough to be fitted to curved corners and circular vision panels. Tested with many popular glass types. Supplied coiled in a box so it's easily dispensed and cut to length, reducing wastage.



LG1721



For 44mm thick doors or rebated screen frames.



LG1720



For unrebated screen frames.



### Test evidence

Fire: BS EN 1634-1: 2014.  
Fire: BS 476-22: 1987.

### Performance

Provides 60 minutes fire resistance.

### Size

22mm x 20mm.

### Standard lengths

30m coils.

### Seal material

Sodium silicate intumescent.

### Finish

Black with orange identification spine.

### Glass thickness

Suitable for use with 14mm - 16mm fire rated glass.

### Glass type

Please refer to Certifire certificate CF5060 for the full range of glass types.

### Application

Doors and screens.  
FD30 + FD60 fire doors.

### Intumescent liner

Liner is required for flaxboard substrates below 500kg/m<sup>3</sup>.

### Glazing beads

Glazing beads are required on both sides of the glass.

Note: Hardwood or softwood beads are available (min density 550kg/m<sup>3</sup>).

Fixing of beads: Screwed using No.8 x 45mm countersunk screws at 200mm nom. centres.

### Accreditation

