



FIREPROTECT

## Data Sheet

Fireprotect House  
Factory Road  
Sandycroft  
Deeside  
Flintshire  
CH5 2QJ

Tel:- 01244 536595  
Fax:- 01244 533592  
e-mail:- [sales@fireprotect.co.uk](mailto:sales@fireprotect.co.uk)  
Web:- <http://www.fireprotect.co.uk>

### FDP005 Closed Cell Foam Tape

Manufacturers & Suppliers of Passive Fire Protection Products

#### DESCRIPTION

FDP005 is a black single sided EPDM foam tape with an acrylic adhesive. It benefits from good chemical resistance, and is self-extinguishing approved to FMVSS302.

FDP005 can be used for a wide range of applications requiring a positive water seal and good chemical resistance. It can also be used for open and close seals.

Thicknesses available:- 2, 3, 4, 5, and 6mm  
Width available:- 10, 12 and 15mm



#### TECHNICAL PROPERTIES

* Foam type	EPDM closed cell
* Foam density	130-170kg/m <sup>3</sup>
* Adhesive	Acrylic
* Application temperature	+10°C
* Service temperature	-30°C to +90°C
* Recommended compressions	30%
* Shelf life	2 years when stored in original packaging at 21°C, 50% relative humidity out of direct sunlight.

#### PREPARATION

Ensure surfaces are clean, dry and free from grease, dust, dirt and loose particles.