



FIREPROTECT

Data Sheet



Fireprotect House
Factory Road
Sandycroft
Deeside
Flintshire
CH5 2QJ

Tel:- 01244 536595
e-mail:- enquiries@fireprotect.co.uk
Web:- http://www.fireprotect.co.uk

System - 36/7 Plus

Manufacturers & Suppliers of Passive Fire Protection Products


System-36/7 PLUS is a flexible U-shaped glazing gasket designed for 30 minutes fire resistance in doors and screens. Flexible enough to be fitted to curved corners and circular vision panels. Tested with many popular glass types. Supplied coiled in a box so it's easily dispensed and cut to length, reducing wastage.



LG1321



For 44mm thick doors or rebated screen frames.



LG1320



For unrebated screen frames.



Test evidence

Fire: BS EN 1634-1: 2014.
Fire: BS 476-22: 1987.

Performance

Provides 30 minutes fire resistance.

Size

13mm x 15mm.

Standard lengths

60m coils.

Seal material

Sodium silicate intumescent.

Finish

Black with blue identification spine.

Glass thickness

Suitable for use with 7mm - 8mm fire rated glass.

Glass type

Please refer to Certifire certificate CF5060 for the full range of glass types.

Application

Doors and screens.
FD30 fire doors.

Intumescent liner

Liner is required for flaxboard substrates below 500kg/m³.

Glazing beads

Glazing beads are required on both sides of the glass.

Note: Hardwood beads are available (min density 600kg/m³ for door beading and min 640kg/m³ for screen beading).

Fixing of beads: Pinned using 40mm panel pins at 200mm nom. centres.

Accreditation

